0003·TDS ~ Temperature sensor

Description


The module **0003·TDS** is specially designed for measuring temperatures in the range -55 ° C ~ 125 ° C, especially suitable for temperature monitoring in low temperature ovens and preservation processes.

It is based on a monolithic chip that offers a resolution of 0,07ºC with an error in the range of -10° C to 85° C (+ -) 0.5° C.

Parameters

Parameter	Minimum	Typical	Maximum	Unit
Temperature Range	-55		125	ºC
Measurement Error (-10~85ºC)			±0,5	ºC
Measurement Error (-55~125ºC)			±2,0	ºC

Connections



The measuring probes of this device are of the DS18B20 type, its power is 3.3V and communicate with the equipment through a single cable, in the image you can see one of the probes that we supplied with the device.



The auxiliary terminals has the power supply terminals, gnd and positive, and terminal communications with the probe.

Particular attention must be paid to the connection, it must be as stable as possible, the connection cable will be less than 3 meters and the measuring element, the chip, must be protected from weather agents.

Startup

Configuration

Use

From:
https://doc.caixadesoft.es/ - **Documentación**

Permanent link:
https://doc.caixadesoft.es/doku.php?id=en:0003:tds&rev=1507397279

Last update: **07/10/2017 17:27**